

高圧ガス入りランプ製品ラインナップ

Wire Terminal

Bulb	Filament type	Base/ Assembly	Bulb dia. (mm)	Volts (V)	Amps (A)	Watts (W)	MSCP (cd)	Life (h)
T-1	C-2R	WT	3	2.4	0.42	1	0.85	12
T-1	C-2R	WT	3	2.4	0.4	1	0.85	8
T-1	C-2R	WT	3	2.9	0.6	1.7	1.15	25
T-1	C-2R	WT	3	3.5	0.72	2.5	2.5	50
T-1 1/4	C-2R	WT	4	2.4	0.39	0.9	0.74	20
T-1 1/4	C-2R	WT	4	3.5	0.72	2.5	2.5	50
T-1 1/2	SC-2R	WT	4.5	12	0.5	6	8.5	70
T-1 1/2	C-6	WT	4.8	2.6	0.69	1.8	1.75	8
T-1 1/2	C-6	WT	5	4.8	1.1	5.3	9.2	25
T-1 3/4	C-6	WT	5.5	4.8	1.16	5.6	8.8	20
T-2 1/2	C-2R	WT	7	12	0.25	3	2.07	5,000
T-2 1/2	C-2R	WT	7	13.5	0.23	3	2.62	2,000
T-2 1/2	C-6	WT	7.2	9.8	1.1	10.8	18	50
T-2 1/2	C-6	WT	7.3	3.7	0.79	2.9	4.2	12
T-2 1/2	C-6	WT	8	4.8	1.1	5.3	8.1	25
T-2 1/2	C-8/C-8	WT	8	6	1.33	8	12.5	100
T-2 1/2	C-6	WT	8	7.2	1.1	7.9	15	20

Bayonet

Bulb	Filament type	Base/ Assembly	Bulb dia. (mm)	Volts (V)	Amps (A)	Watts (W)	MSCP (cd)	Life (h)
T-2 1/4	CC-6	BA8s	7	28	0.36	10	6.25	4,000
T-2 1/2	CC-6' (R)	BA9s	7	6	2	12	19	50
T-2 1/2	CC-6' (R)	BA9s	7	6	1.67	10	11.76	5,100 1)
T-2 1/2	C-8Z	BA9s	7	12	0.83	10	8.5	10,000
T-2 1/2	CC-6' (R)	BA9s	7	28	0.36	10	6.25	10,000
T-2 1/2	CC-6' (R)	BA9s	7	28	0.36	10	8	10,000
T-2 1/2	CC-6' (R)	BA9s	7	28	0.43	12	10.4	62,000 1)
T-2 1/2	CC-6' (R)	BA15s	7	28	0.36	10	8	10,000

Note 1) : Life at AC